Blixer® 23



SALES FEATURES

Blixer 23 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 23. 3-phase. Power 6 HP. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 24 Qt. stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 20 to 75 portions (7 oz.) and more.

Select your options at the back page, F part.

C TECHNICAL DATA	
Output power	6 HP
Electrical data	208-240V/60/3
Speeds	1800 and 3600 rpm
Dimensions (H×L×W)	48 1/16" × 23 5/8" × 26 3/8"
Rate of recyclability	95%
Net weight	309 lbs
Nema #	L15-30P
Reference	BLIXER 23 A - 208-240V/60/3

Number of 7 oz portions :	20 to 75 portions
Quantity processed per operation	8 to 33 lbs

PRODUCT FEATURES / BENEFITS

MOTOR BASE

- Induction direct drive motor for intensive use.
- Power 6 HP.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- 2 speeds : 1800 and 3600 rpm.
- Pulse function for a better cut precision.

CUTTER FUNCTION

- Removable and tiltable 24 Qt. bowl for effortless emptying and cleaning.
- Bowl-base blade assembly with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Stainless-steel construction for making cleaning easier.
- Timer from 0 to 15 minutes for a better preparation control.
- Transparent lid with bowl scraper to improve the end-product consistency and with a lid wiper to enable user to monitor processing.
- Opening in center of lid for adding liquid or dry ingredients during processing.
- 3 retractable wheels making it easier to move the appliance in order to clean the surface.

INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels

STANDARDS

ETL electrical and sanitation Listed/cETL



Slixer® 23



Blixer® 23

F


OPTIONAL ATTACHMENTS


- Fine serrated edge stainless steel "S" Blade Ref. 57071
- Complete Bowl Assembly Ref. 59155


G

ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.







3lixer® 23